

Płyta główna ASROCK B850M Steel Legend WiFi AM5 DDR5 mATX MB

Cena brutto: 791,00 zł

Cena netto: 643,09 zł

Koszty wysyłki: GRATIS od 100 PLN przy płatności przelewem / +15 zł pobranie.

Unique Feature

Superb Productivity

- PCIe Gen5 (Graphics, M.2)

- Dual Channel DDR5

Rock-Solid Durability

- 12+2+1 Power Phase, Dr.MOS for VCore+SOC+MISC with Enlarged Heatsink Armor

- Flexible Integrated I/O Shield

- 20K Long-lasting Black Caps (high quality and conductive polymer capacitors)

Ultrafast Connectivity

- 2.5G LAN, 802.11be Wi-Fi 7 Module

EZ Update

- BIOS Flashback Button

- ASRock Auto Driver Installer

EZ Troubleshooter

- ASRock Post Status Checker

CPU

- Supports AMD Socket AM5 Ryzen™ 9000, 8000 and 7000 Series Processors*

Chipset

- AMD B850

Memory

- Dual Channel DDR5 Memory Technology

- 4 x DDR5 DIMM Slots

- Supports DDR5 ECC/non-ECC, un-buffered memory up to 8000+ (OC)
- Max. capacity of system memory: 256GB
- Supports Extreme Memory Profile (XMP) and EXTENDED Profiles for Overclocking (EXPO) memory modules

BIOS

- 256Mb AMI UEFI Legal BIOS with GUI support

Graphics

Integrated AMD RDNA™ graphics (Actual support may vary by CPU)

- 1 x HDMI 2.1 TMDS/FRL 8G Compatible, supports HDR, HDCP 2.3 and max. resolution up to 4K 120Hz
- 1 x DisplayPort 1.4 with DSC (compressed), supports HDCP 2.3 and max. resolution up to 4K 120Hz

Audio

- 7.1 CH HD Audio with Content Protection (Realtek ALC1220 Audio Codec)
- Impedance Sensing on Rear Out port
- Individual PCB Layers for R/L Audio Channel
- Nahimic Audio

LAN

- 2.5 Gigabit LAN 10/100/1000/2500 Mb/s
- Dragon RTL8125BG
- Supports Dragon 2.5G LAN Software
- Smart Auto Adjust Bandwidth Control
- Visual User Friendly UI
- Visual Network Usage Statistics

- Optimized Default Setting for Game, Browser, and Streaming Modes

- User Customized Priority Control

Wireless LAN

- 802.11be 2x2 Wi-Fi 7 Module
- Supports IEEE 802.11a/b/g/n/ac/ax/axe/be
- Supports 2.4GHz/5GHz/6GHz* frequency band
- Supports 160MHz channel bandwidth with 6GHz* frequency band

- 1 antenna to support 2 (Transmit) x 2 (Receive) diversity technology

- Supports Bluetooth 5.4

- Supports MU-MIMO

Slots

CPU:

- 1 x PCIe 5.0 x16 Slot (PCIE1), supports x16 mode*

- 1 x PCIe 4.0 x4 Slot (PCIE2), supports x4 mode*

Chipset:

- 1 x Vertical M.2 Socket (Key E), supports type 2230 WiFi/BT PCIe WiFi module

- 15 μ Gold Contact in VGA PCIe Slot (PCIE1)

Storage

CPU:

- 1 x Blazing M.2 Socket (M2_1, Key M), supports type 2280 PCIe Gen5x4 (128 Gb/s) mode*

Chipset:

- 1 x M.2 Socket (M2_2, Key M), supports type 2260/2280 PCIe Gen4x2 (32 Gb/s) mode*

- 1 x Hyper M.2 Socket (M2_3, Key M), supports type 2260/2280 PCIe Gen4x4 (64 Gb/s) mode*

- 4 x SATA3 6.0 Gb/s Connectors

RAID

- Supports RAID 0, RAID 1 and RAID 10 for SATA storage devices

- Supports RAID 0, RAID 1 and RAID 10 for M.2 NVMe storage devices*

USB

CPU:

- 1 x USB 3.2 Gen2 Type-C (Rear)

- 1 x USB 3.2 Gen2 Type-A (Rear)

- 1 x USB 3.2 Gen1 Type-A (Rear (USB32_2))

Chipset:

- 1 x USB 3.2 Gen1 Type-C (Front)

- 5 x USB 3.2 Gen1 Type-A (1 Rear (USB32_3), 4 Front)

Connector

- 8 x USB 2.0 (4 Rear, 4 Front)
- 1 x SPI TPM Header
- 1 x Thermistor Cable Header
- 1 x Power LED and Speaker Header
- 1 x RGB LED Header*
- 3 x Addressable LED Headers**
- 2 x CPU Fan Connectors (4-pin) (Smart Fan Speed Control)***
- 3 x Chassis Fan Connectors (4-pin) (Smart Fan Speed Control)***
- 1 x 24 pin ATX Power Connector (Hi-Density Power Connector)
- 1 x 8 pin 12V Power Connector (Hi-Density Power Connector)
- 1 x 4 pin 12V Power Connector (Hi-Density Power Connector)
- 1 x Front Panel Audio Connector
- 2 x USB 2.0 Headers (Support 4 USB 2.0 ports)
- 2 x USB 3.2 Gen1 Headers (Support 4 USB 3.2 Gen1 ports)
- 1 x Front Panel Type C USB 3.2 Gen1 Header

Rear Panel I/O

- 2 x Antenna Ports
- 1 x HDMI Port
- 1 x DisplayPort 1.4
- 1 x USB 3.2 Gen2 Type-C Port (10 Gb/s)
- 1 x USB 3.2 Gen2 Type-A Port (10 Gb/s)
- 2 x USB 3.2 Gen1 Ports
- 4 x USB 2.0 Ports
- 1 x RJ-45 LAN Port
- 1 x BIOS Flashback Button
- HD Audio Jacks: Line in / Front Speaker / Microphone

Software and UEFI

Software

- ASRock Motherboard Utility (A-Tuning)

- ASRock Dragon 2.5G LAN Software

- ASRock Polychrome SYNC*

UEFI

- ASRock EZ Mode

- ASRock Full HD UEFI

- ASRock Auto Driver Installer

- ASRock Instant Flash

- 2 x SATA Data Cables

- 2 x ASRock WiFi 2.4/5/6 GHz Antennas

- 1 x Thermistor Cable

- 2 x Screws for M.2 Sockets

- 1 x Standoff for M.2 Socket

Accessories

Form Factor

- Micro ATX Form Factor: 9.6-in x 9.6-in, 24.4 cm x 24.4 cm

